


1406 **ALMA**


CARACTERISTICS

360° uniform beam angle (0 to -20°).

- Colourless anodised machined aluminium body
- Vandalproof organic glass window
- 316L Stainless steel screws
- Attaches directly to roadway or to recess plate (not available in 230V version)
- Supports occasional road traffic by any type of vehicle







Number of LEDs	6
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/1406z-alma-r1029

APPLICATION

Marker-lighting

CONFIGURATEUR.EMPLACEMENT

Wall lights

Ground recessed fittings

CARACTERISTICS

Weight: **780** g

Options of luminous effects



faisceau incliné bas



Transparent flat window

Power supply - Control



Cable length: 1 m

Integrated: 24V-Non dimmable, 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

Integrated: 230V-Non dimmable, 230V-0/10V

Material



(AL) Anodised glazed aluminium




Vandalism-proof organic glass

Mechanical strength - Waterproofness Protrusion which is an

obstacle for 2-wheels



vehicles and pedestrians. The unit should be permanently lit to draw attention to the obstacle.



vehicles traffic IK10 Resists impacts up to IK10

20J 20J

Tight for temporary immersion