PRODUCT DATASHEET

5781MAM PASSY

Linear spotlight for recessing in public spaces. Can be ordered in two lengths, installed individually or as a continuous line. Externally adjustable tiltable LED plate (0° to 25°) without without opening the fitting or compromising its water resistant. Device swivels in its recess for the opposite direction. Clips in with no screws for vandalproof installation.

APPLICATIONS:

- Medium height facade lighting (10m)
- Highlight architectural features, street furniture, trees...
- Squares and public spaces

CARACTERISTICS

Lenght = 1 m Blue, white and red LEDs installed to reproduce the French flag. For Memorial, Government building facade lighting.

- Colourless anodised aluminium body
- Vandalproof organic glass window
- Flush-recessed
- Extruded aluminum profiled recess plate and accessories for continuous line or independent installation
- Cavity in the recess for running the cable and connectors
- Withstands occasional traffic from all kinds of vehicles
- RGBW options available
- anti-glare option available

CONFIGUR Grou Grou Grou CARACTER Weig Options of ① Adju: ① Adju: ① Adju: ① Adju: ① Controls of ② Controls of ③ Controls of ④ Controls of ③ Controls of ④ Controls o

Number of LEDs

27

Select your specific requirements with our product configurator, by filtering technical criteria at the following link: http://www.lec-lyon.com/5781mam-passy-r1271




APPLICATION	
W	Outdoor lighting
This vo output optic,	ard flux : 6021 lm alue is gained from the optimum t of the LED number, inclusive of for a cool white LED (6000K) GURATEUR.EMPLACEMENT
	Ground flush recessed fittings
L_	Ground recessed fittings
CARACTERISTICS	
	Weight : 6000 g
Optio	ons of luminous effects
	Adjustable on 1 axis
	Rotating beam
	Transparent flat window
Powe	r supply - Control
~	Cable length: 1 m
	Integrated : 24V-Non dimmable
	Integrated : 230V-Non dimmable
Material	
AL	Anodised glazed aluminium
2	Vandalism-proof, scratch- proof, UV-proof, polycarbonate window, M2
Mech	anical strength - Waterproofness
0	Withstands random all vehicles traffic
4 T	Resists compression up to 4 tons
IK10 60J	Resists impacts up to IK10 60J
IP68	Tight for extended immersion
P	Adjustable orientation without dismantling

Technical data is subject to changes. Luminaire guaranteed 5 years. Luminaire designed and manufactured in France.



5781MAM PASSY

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/5781mam-passy-r1271



PDF generated on 10.08.2025

www.lec-lyon.com

Technical data is subject to changes. Luminaire guaranteed 5 years. Luminaire designed and manufactured in France.