

1843SF PALAIS ROYAL

LED spotlight surface-mounted on roadways for raking or extensive illumination.


APPLICATIONS:

- Cycle paths and pedestrian paths lighting
- Roadway lighting
- Public space lighting
- Low facades lighting
- Footbridges and piers

CARACTERISTICS

1 beam direction

- Colourless anodised machined aluminium body
- Vandalproof organic glass window
- 316L Stainless steel screws
- Mounted directly on roadway or to recess plate
- Withstands occasional traffic from all kinds of vehicles



Number of LEDs	2
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:
<http://www.lec-lyon.com/1843sf-palais-royal-r1311>

APPLICATION

Outdoor lighting

Standard flux : 210 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

CONFIGURATEUR.EMPLACEMENT

- Ground recessed fittings
- Pavements sides

CARACTERISTICS

Weight : 715 g

Options of luminous effects

- Non adjustable
- Paralell beam
- Beam with various openings
- Transparent flat window

Power supply - Control

- Cable length: 1 m
- Integrated** : 24V-PWM
Remote : 24V-0/10V, 24V-DMX, 24V-DALI
- Integrated** : 230V-Non dimmable

Material

- AL** Anodised glazed aluminium
- PC 2** Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2

Mechanical strength - Waterproofness

- Obstacle** : Protusion which is an obstacle for 2-wheels vehicles and pedestrians. The unit should be permanently lit to draw attention to the obstacle.
- 8T** Withstands random all vehicles traffic
- 20** Withstands low-speed light vehicles traffic
- EIN** Certified in compliance with European Standards 60598-2-22 for emergency lighting units
- 8T** Resists compression up to 8 tons
- IK10 40J** Resists impacts up to IK10 40J
- IP68** Tight for extended immersion

1843SF PALAIS ROYAL

This datasheet gives you all the available optics for this product, consistent with the number of LEDs.
URL of this product: <http://www.lec-lyon.com/1843sf-palais-royal-r1311>

