

4010 **LUMINY**

«Mini» version in the Luminy spotlight range.

Installs on roads/floors, wall or poles with bespoke accessories.


APPLICATIONS:

- Highlight architectural features
- Highlight landscapes
- Path, alley, street furniture

CARACTERISTICS

- · Anodised machined aluminium body
- Vandalproof organic glass window
- 316L Stainless steel bracket and screws
- Thermolacquered bracket on request





Number of LEDs	1
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/4010-luminy-r136

APPLICATION

Outdoor lighting

Standard flux: 223 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

CONFIGURATEUR.EMPLACEMENT

Wall lights



Masts

CARACTERISTICS

Weight: 220 g

Options of luminous effects



(2) Adjustable on 2 axis



Rotating beam



Beam with various openings



Transparent flat window

Power supply - Control



Cable length: 1 m

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

Material



(AL) Anodised glazed aluminium



Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2

Mechanical strength - Waterproofness

IK10 Resists impacts up to IK10

Tight for temporary IP67 immersion



4010 LUMINY

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/4010-luminy-r136

