


# 1844CR1 **SAINT RAPHAEL**


#### CARACTERISTICS

Fireproof safety cable CR1-C1

- · Cast aluminium body
- Vandalproof organic glass
- 316L Stainless steel screws
- Attaches directly to roadway or to recess plate







Number of LEDs	24
Type of LEDs	Wide angle 5 mm LEDs (H)
Color(s)	Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/1844cr1z-saint-raphael-r2124

### APPLICATION

Marker-lighting

#### **CONFIGURATEUR.EMPLACEMENT**



Ground recessed fittings

### **CARACTERISTICS**

Weight: 570 g

### **Options of luminous effects**



(x) Non adjustable



Paralell beam



Transparent dome (optional)

# **Power supply - Control**



Cable length: 2 m CR1

Integrated: 24V-PWM **Remote:** 24V-0/10V, 24V-DMX, 24V-DALI



Marine anodised cast aluminium

## Mechanical strength - Waterproofness

IP69 pressure water spray (previous registration)

> Protrusion which is an obstacle for 2-wheels



vehicles and pedestrians. The unit should be permanently lit to draw attention to the obstacle.



Withstands low-speed light vehicles traffic



Certified in compliance with European Standards 60598-2-22 for emergency lighting units

Resists compression up to 2,5 tons

IK10 Resists impacts up to IK10 60J 60J

Tight for extended immersion IP68