

5782 **PASSY**

Linear spotlight for recessing in public spaces. Can be ordered in two lengths, installed individually or as a continuous line. Externally adjustable tiltable LED plate (0° to 25°) without without opening the fitting or compromising its water resistant. Device swivels in its recess for the opposite direction. Clips in with no screws for vandalproof installation.

APPLICATIONS:


- Medium height facade lighting (10m)
- Highlight architectural features, street furniture, trees...
- · Squares and public spaces


CARACTERISTICS


Length = 530 mm

- Colourless anodised aluminium body
- Vandalproof organic glass window
- Flush-recessed
- Extruded aluminum profiled recess plate and accessories for continuous line or independent installation
- Cavity in the recess for running the cable and connectors
- Withstands occasional traffic from all kinds of vehicles
- RGBW options available
- anti-glare option available









| Number of LEDs | 16 |
|----------------|--|
| Type of LEDs | Power LEDs. Contact us for hot countries. |
| Color(s) | Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K) |

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/5782-passy-r2433

APPLICATION



Outdoor lighting

Standard flux: 3568 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

CONFIGURATEUR.EMPLACEMENT

Ground flush recessed fittings

Ground recessed fittings


CARACTERISTICS

Weight: 3300 g


Options of luminous effects




RGBW option












Power supply - Control

Cable length: 0.53m

Integrated: 230V-Non dimmable, 230V-0/10V, 230V-DMX, 230V-DALI

Material

(AL) Anodised glazed aluminium



Mechanical strength - Waterproofness




Withstands random all vehicles traffic

Resists compression up to 4 tons IK10 Resists impacts up to IK10

60J 60J Tight for extended

IP68 immersion





5782 PASSY

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/5782-passy-r2433

