

4059 **LUMINY 6**

«Extra» version in the Luminy spotlight range.

Installs on roads/floors, wall or poles with custom-adaptable accessories.


APPLICATIONS:

- Architectural heritage enhancement
- Facades lighting
- Tree and vegetation uplighting
- · Direct or indirect lighting of public space

CARACTERISTICS Optic 4°, monochromatic only

- Aluminium body with thermolacquered paint finish, RAL of your choice
- Vandalproof organic glass window
- 316L Stainless screws
- 3-way orientable
- · Optional light hood





Number of LEDs	16
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/4059-luminy-6-r2444

APPLICATION

Outdoor lighting

Standard flux: 7243 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

CONFIGURATEUR.EMPLACEMENT

Wall lights



Masts

CARACTERISTICS

Weight: 5300 g

Options of luminous effects



(3) Adjustable on 3 axis



Rotating beam



Transparent flat window

Power supply - Control



Cable length: 5 m

Integrated: 230V-Non dimmable, 230V-0/10V, 230V-DALÍ

Material



Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2

Mechanical strength - Waterproofness

IK10 Resists impacts up to IK10 **20J** 20J

Tight for temporary immersion

OPTIC DATASHEET



4059 LUMINY 6

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/4059-luminy-6-r2444

