

4661 **CORSICA**

Spotlight developed for illuminating facades, with a compact design and optimised for uniform wall-washing.

APPLICATIONS:


- · Facade, monument lighting
- Tree and vegetation uplighting
- · Direct or indirect lighting of public space


CARACTERISTICS

Luminous module of the 4660 with ground mounting plate that integrates power supply and control.

- · Aluminium body with thermolacquered paint finish, RAL on request
- Vandalproof organic glass window
- Fixed or adjustable arm (max 1m)
- Tilt adjustment: +/- 90° around the 2-way-locking ball & socket and +/- 15° around the arm
- Remote power & control unit (except 4661)
- · Optional light hood
- RGBW options available







APPLICATION

Outdoor lighting

Standard flux: 9366 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

CONFIGURATEUR.EMPLACEMENT

Wall lights

CARACTERISTICS

Weight : 5000 g

Options of luminous effects



RGBW option



(2) Adjustable on 2 axis



Rotating beam



Beam with various openings



Transparent flat window



Colour control system (optional)

Power supply - Control



Cable length: 0

Integrated: 230V-Non dimmable, 230V-PWM, 230V-0/10V, 230V-DMX, 230V-DALI

Material



Marine anodised cast aluminium



Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2

Mechanical strength - Waterproofness

IK10 Resists impacts up to IK10

20J 20J

Tight for temporary



Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/4661-corsica-r2445



4661 CORSICA

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/4661-corsica-r2445

