

5752 **CLEM-IN**

Linear recessed projector for public spaces.

Orderable in 4 lengths, it allows individual continuous line or installations.

With the very extensive asymmetrical optics, homogeneous lighting is obtained even for a grazing installation.


Anti-vandalism installation clipping (no screw).

CARACTERISTICS

Length with recess = 1500mm

Vandal-proof organic glass profile Clear anodized aluminum sheath Without protrusion Cable outlet on the underside 18 LEDs 700mA controlled in PWM Four-color option possible: 4x12 350mA LEDs controlled in PWM







| Number of LEDs | 18 |
|----------------|--|
| Type of LEDs | Power LEDs. Contact us for hot countries. |
| Color(s) | Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K) |

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/5752-clem-in-r2515

APPLICATION





Outdoor lighting

Standard flux: 4014 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

CONFIGURATEUR.EMPLACEMENT





CARACTERISTICS

Weight : 1100 g

Options of luminous effects




RGBW option





Beam with various openings



Colour control system




Power supply - Control

Cable length: 1 m

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

Material

(AL) Anodised glazed aluminium



Mechanical strength - Waterproofness



Withstands ran vehicles traffic Withstands random all

IK10 Resists impacts up to IK10

Tight for temporary



5752 CLEM-IN

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/5752-clem-in-r2515

