


# 1810B **SAVOIE**


#### CARACTERISTICS

Fitted with a connecting box with one or two cable glands for in-line connection.

- Organic glass lens
- · Stainless steel mirror back
- Aerodynamic shape to reduce particle deposits and permit easy cleaning with water.
- Materials unaffected by corrosive atmosphere in tunnels
- Beams angled 45°
- Fireproof safety cable CR1-C1 optional







#### Number of LEDs 24 Type of LEDs Wide angle 5 mm LEDs (H) Warm white 3000K (E), Neutral white 4000K (N), Cool white Color(s) 6000K (W), Red (R), Amber (O), Green (V), Blue (L)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/1810bz-savoie-r848

### **APPLICATION**

Marker-lighting

### **CONFIGURATEUR.EMPLACEMENT**

Wall lights

### **CARACTERISTICS**

### **Options of luminous effects**



(X) Non adjustable



Inclined beam



Paralell beam



Transparent flat window

### **Power supply - Control**



Cable length: 1 m

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

Integrated: 230V-Non

## dimmable

#### Material



Vandalism-proof, UV-proof, polycarbonate window

### **Mechanical strength - Waterproofness**

IP69 pressure water spray (previous registration)



Certified in compliance with European Standards 60598-2-22 for emergency lighting units

IK10 Resists impacts up to IK10 40J

40J

Tight for temporary immersion