

1830KM **LUCERNE**

«Medium» version in the round flush recessed raking light range. Choice of lighting effects for customised LED marker-lighting.

APPLICATIONS:


- Decorative or safety markerlighting
- Installed at regular intervals to mark a path, cycle path, stairs
- Public space enhancement

CARACTERISTICS

The flange hides recess plate imperfections. Angled LED with internal mirror for 360° flush raking

- Anodised aluminium body
- Vandalproof organic glass window
- 316L Stainless steel screws
- Flush-recessed (except 1830K and 1830D)





APPLICATION

Marker-lighting

CONFIGURATEUR.EMPLACEMENT

Ground recessed fittings

CARACTERISTICS

Weight: 450 g

Options of luminous effects



(1) Adjustable on 1 axis



Inclined beam



Transparent flat window

Power supply - Control

Cable length: 1 m

Integrated: 24V-PWM **Remote:** 24V-0/10V, 24V-DMX, 24V-DALI



(AL) Anodised glazed aluminium



316L Stainless steel



Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2

Mechanical strength - Waterproofness

IK10 Resists impacts up to IK10

60J 60J

Tight for extended immersion IP68

Number of LEDs	16
Type of LEDs	Wide angle 5 mm LEDs (H)
Color(s)	Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/1830kmz-lucerne-r970